


# EMERGENCY LIGHTS UFO

LED Non-maintained surface mount high lumen output emergency light



• UF.10.NC120.NM



Dimension: mm NTS  
**High Power L.E.D**

## TECHNICAL DATA

Mode of Operation	: Non-Maintained
Lamp	: 10W High Power LED Module
Rated Duration	: 2hrs and others
Mains Supply	: 230 Volts, 50/60Hz
Power Consumption	: < 2.2W
Battery	: High temp Nickel Cadmium
Charge Monitor	: Green LED Ø5mm
Test Facility	: Micro switch
Safety Feature	: Low volt cut-off preventing battery overdischarge
Fitting Construction	: Electro galvanised steel with epoxy powder coating
Mounting	: Ceiling
Cable Entry	: Ø20mm K/O hole
Weight	: 1.5kg (gross)
Compliance	: SS 563 : Part 1 & 2, SS IEC 60598-2-22
Warranty	: 1 year

## KEY FEATURES

- > High Brightness Output
- > High Lumen/watt Efficiency
- > Low Power Consumption
- > Low Maintenance
- > Long Lifespan
- > Mainly use for high ceiling (> 8 meters)

## ORDERING GUIDE (Please check with Sales Dept if customisation is required)

Model	Lamp	Battery type
UF.10.NC120.NM	10W LED Module	Nickel Cadmium



Surface Mount  
Emergency Luminaire



Specifications subject to changes without prior notice.

