
EMERGENCY EXIT LIGHTS





Dimension: mm NTS

TECHNICAL DATA

Mode of Operation : Maintained

Lamp Maxspid 1W SMT LED Lamp

Rated Duration 2hrs and others Mains Supply 230 Volts, 50/60Hz

Power Consumption: < 3W

Battery : High temp Nickel Cadmium

: Green LED Ø5mm Charge Monitor Test Facility : Push button switch

Safety Feature : Low volt cut-off preventing battery overdischarge

Housing & Diffuser : Injection moulded fire retardant, high impact polycarbonate Mounting Wall, ceiling suspended or semi-recessed

Ø20mm K/O hole Cable Entry Weight 1.6kg (gross)

SS 563: Part 1 & 2, SS IEC 60598-2-22 Compliance

Warranty

KEY FEATURES

- > Using Surface Mount Technology LED
- > High Durability & Reliability
- > Low Heat
- > Low Maintenance
- > Low Power Consumption
- > No "Black Ends"





IP65 CLASS I

ORDERING GUIDE (Please check with Sales Dept if customisation is required)

Single Sided	Legend
KL/M/W5100	EXIT
KL/M/W5100 (R)	EXIT►
KL/M/W5100 (L)	▼ EXIT
KL/M/W510RM	Ž.
KL/M/W510RM (E)	₽
KL/M/W510RM (W)	← 🔁

^{*}Heating strip applicable (for cold room used)



