

EMERGENCY LIGHTS UFO



LED Non-maintained recess / surface mount emergency light







• UPCR.3.NC180.NM

• with Big Disk Adaptor

• with Surface Casing



UPCR.3.NC180.NM



with Big Disk Adaptor

with Surface Casing

TECHNICAL DATA

- Mode of Operation : Non-Maintained
- Lamp : 3W High Power LED
- Rated Duration : 3 hrs and others
- Mains Supply : 230 Volts, 50/60Hz
- Power Consumption : < 1.4W
- Battery : High temp Nickel Cadmium
- Charge Monitor : Green LED
- Test Facility : Tactile switch
- Safety Feature : Low volt cut-off preventing battery overdischarge
- Fitting Construction : Injection moulded fire retardant high impact polycarbonate
- Mounting : Recess/Surface
- Weight : 0.19kg (gross)
- Compliance : SS 563 : Part 1 & 2, SS IEC 60598-2-22
- Warranty : 1 year

ORDERING GUIDE (Please check with Sales Dept if customisation is required)

Model	Lamp	Battery type
UPCR.3.NC180.NM	3W LED	Nickel Cadmium

Dimension: mm NTS

High Power L.E.D

KEY FEATURES

- > High Brightness Output
- > High Lumen/watt Efficiency
- > Low Power Consumption
- > Low Maintenance
- > Long Lifespan



Type and batch tested with
PSB PLS-LISTED LABEL



Recess Mount/
Surface Mount
Emergency Luminaire
Ø78 /
Ø78-Ø100mm



IP20 (Body)
IP54 (Disk)

16

Specifications subject to changes without prior notice.