









● UPCR.3.NC180.NM

● with Adaptor

● with Surface Kit



UPCR.3.NC180.NM



with Adaptor

with Surface Kit

### TECHNICAL DATA

Mode of Operation	: Non-Maintained
Lamp	: 3W High Power LED
Rated Duration	: 3 hrs and others
Mains Supply	: 230 Volts, 50/60Hz
Power Consumption	: < 1.4W
Battery	: High temp Nickel Cadmium
Charge Monitor	: Green LED
Test Facility	: Tactile switch
Safety Feature	: Low volt cut-off preventing battery overdischarge
Fitting Construction	: Injection moulded fire retardant high impact polycarbonate
Mounting	: Recess/Surface
Weight	: 0.19kg (gross)
Compliance	: SS 563 : Part 1 & 2, SS IEC 60598-2-22
Warranty	: 1 year

### ORDERING GUIDE (Please check with Sales Dept if customisation is required)

Model	Lamp	Battery type
UPCR.3.NC180.NM	3W LED	Nickel Cadmium

Dimension: mm NTS

**High Power L.E.D**

### KEY FEATURES

- > High Brightness Output
- > High Lumen/watt Efficiency
- > Low Power Consumption
- > Low Maintenance
- > Long Lifespan



Type and batch tested with  
PSB PLS-LISTED LABEL



Ø78 /  
Ø78-Ø100mm

Recess Mount/  
Surface Mount  
Emergency Luminaire



IP20 (Body)  
IP54 (Disk)

